



GENERAL NOTES:

- I. INSTALL 26"H x 19"D CABLE TRENCH, COMPLETE WITH CABLE DIVIDER.
- CABLE TRENCH MUST PASS BETWEEN EXISTING STEEL STRUCTURE FOUNDATION AND PROPOSED P56 BREAKER FOUNDATION.

-FOR CONTROL BUILDING ENTRANCE SEE DETAIL 6 E-18

NOTES:

- 1. THIS WORK TO BE COMPLETED UNDER ADD ALTERNATE #3. CONTRACTOR WILL REMOVE EXISTING CABLE TRENCH, ONCE ALL ASSOCIATED CABLES HAVE BEEN ABANDONED, REMOVED, OR RELOCATED. ALL DISTURBED AREAS WILL BE REPAIRED AS NECESSARY TO MATCH EXISTING GRADE.
- 2. THIS WORK TO BE COMPLETED UNDER ADD ALTERNATE #3. CONTRACTOR WILL REMOVE OUTDOOR PANEL #1 AND #2 FOUNDATION AND CABINETS ONCE ALL ASSOCIATED EQUIPMENT HAS BEEN ABANDONED, REMOVED, OR RELOCATED.
- 1. INSTALL CONDUITS BETWEEN THE CABLE
 TRENCH AND EQUIPMENT BY THE MOST DIRECT
 ROUTE THAT WILL NOT INTERFERE WITH OTHER
 STRUCTURES OR EQUIPMENT. WHERE MULTIPLE
 CABLES ARE TO BE ROUTED BETWEEN THE
 CABLE TRENCH AND EQUIPMENT, COMBINE
 CABLES WITH LIKE USAGE (POWER, CONTROL,
 AND COMMUNICATIONS) AND INSTALL EACH
 GROUP IN A SINGLE OR MULTIPLE CONDUITS
 SIZED SO THAT THE CONDUIT FILL LIMITATIONS
 OF THE NATIONAL ELECTRIC CODE CHAPTER 9,
 TABLE 1 ARE NOT EXCEEDED.

RECORD DRAWING

By RODGE N. WARRING

COST MALE AND COST ACT 2010

L							
						DESIGNED	AO
L						DEGIGITED	
ſ						004444	40
ľ						DRAWN	AO
ľ							
t	LTR.	DATE	REVISIONS	BY	APPRD.	CHECKED	PW



PROVED BY	DATE AUG 2009	PROJECT NO. 07602-032-01
HIL WEBER F # 36601	SCALE 1"=8'	DWG. NO. E-17